







LKX LP



Standard equipment:

- 3.700.0030 Gun M22 - 3/8" with rotating coupling. (mod. 1310 LP). 
- 6.601.0001 Gun S'10 3/8" M with quick connection (mod. 1515 LP-2015 LP). 
- 3.701.0015 Lance M22 high/low pres. (mod. 1310 LP). 
- 6.602.0044 Lance 900 mm with quick connection. (mod. 1515 LP-2015 LP). 
- 3.103.0050 Nozzle type 045 (mod. 1310 LP)
- 3.103.0053 Nozzle type 060 (mod. 1515 LP)
- 3.103.0050 Nozzle type 045 (mod. 2015 LP)
- 4.618.0143 H. P. hose 10 m 
- Power cable 5 m 

Optional:

- 6.608.0004 Hose reel with brake (hose not included)
- On request models with header tank and/or antiscaling device.
- 3.697.0044 Antiscaling LC-PRECAL (pcs. 4 x 5 lt.)

VERSION
60 Hz
AVAILABLE
DETAILS PAGE 33

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (three phase models).
- Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve.
- Low voltage and delayed Total Stop.
- Suction and delivery S/S valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Detergent built-in tank for indirect suction.
- Auxiliary motor for burner.
- Heavy duty steel frame.
- Hose reel with brake **(optional)**.



	LKX 1310 LP	LKX 1515 LP	LKX 2015 LP
code	8.621.0947	8.621.0934	8.621.0935
operat. pressure/max delivery rate	110/150 bar-1595/2175 psi	150 bar-2175 psi	200 bar-2900 psi
abs. power/voltage	3000W - 230V~50Hz 1ph	5500W - 400V~50Hz 3 ph	7300W - 400V~50Hz 3 ph
motor/pump type/RPM	MP3/1450 RPM	MP3/1450 RPM	MP3/1450 RPM
max. temp. inlet/outlet	40/140 °C	40/140 °C	40/140 °C
dimension/weight	94x65x90cm / 112 Kg - 246 lbs	94x65x90cm / 125 Kg - 275 lbs	94x65x90cm / 128 Kg - 282 lbs