

## HyperL GUARANTEED



Model: 1515 LP  
2015 LP  
2021 LP



### Standard equipment:

- 6.601.0001 Gun PRO S'10 3/8" M with quick connection (mod. 1515 LP - 2015 LP - 2021 LP)



- 3.700.0030 Gun M22 - 3/8" with rotating coupling. (mod. 1211 LP)



- 6.602.0044 Lance 900 mm with quick connection (mod. 1515 LP - 2015 LP - 2021 LP)



- 3.701.0015 Lance M22 high/low press. (1211 LP)



- 3.103.0053 Nozzle type 060 (mod. 1515 LP)
- 3.103.0050 Nozzle type 045 (mod. 2015 LP - 1211 LP)
- 3.103.0054 Nozzle type 065 (mod. 2021 LP)



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

### Optional:

- 6.608.0004 Hose reel with brake (hose not included)

### Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling.
- Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in bypass valve.
- Integrated elastic joint, for best pump coupling.
- Low voltage and delayed Total Stop. Suction and delivery S/S valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Detergent built-in tank for indirect suction.
- Auxiliary motor for burner air cooling and mechanical two ways fuel pump.
- Hose reel (**optional**).



**Integrated elastic joint, for best pump coupling**

**VERSION**  
**60 Hz**  
**AVAILABLE**  
**DETAILS PAGE 33**

|                         | HYPER L 1211 LP               | HYPER L 1515 LP               | HYPER L 2015 LP               | HYPER L 2021 LP               |
|-------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| code                    | 8.621.0921                    | 8.621.0907                    | 8.621.0908                    | 8.621.0928                    |
| operat. pressure        | 110/150 bar-1595/2175 psi     | 150 bar-2175 psi              | 200 bar-2900 psi              | 200 bar-2900 psi              |
| delivery rate           | 660 l/h-2.91 GPM              | 900 l/h-3.96 GPM              | 900 l/h-3.96 GPM              | 1260 l/h-5.55 GPM             |
| abs. power/voltage      | 3000W - 230V~50Hz 1 ph        | 5500W - 400V~50Hz 3ph         | 7300W - 400V~50Hz 3ph         | 9700W - 400V~50Hz 3 ph        |
| motor/pump type/RPM     | MP3/1450 RPM                  | MPW5/1450 RPM                 | MPW5/1450 RPM                 | MPW5/1450 RPM                 |
| max. temp. inlet/outlet | 40/140 °C                     | 40/140 °C                     | 40/140 °C                     | 40/140 °C                     |
| dimension/weight        | 94x65x90cm / 109 Kg - 240 lbs | 94x65x90cm / 127 Kg - 280 lbs | 94x65x90cm / 129 Kg - 284 lbs | 94x65x90cm / 131 Kg - 288 lbs |